

Bezúdržbové olověné akumulátory



CT série

AGM

Předpokládaná životnost 5 let při teplotě 20°C



typ	napětí [V]	kapacita [Ah]	délka [mm]	šířka [mm]	výška [mm]	celková výška	připojení	váha [kg]	balení
CT 1-6	6	1	51	42	51,5	58,5	Fast-on 187	0,27	30
CT 1.3-6	6	1,3	97	24	52	59	Fast-on 187	0,3	20
CT 3-6	6	3	66	33	98	104	Fast-on 187	0,59	16
CT 3.4-6	6	3,4	134	34	60	67	Fast-on 187	0,62	-
CT 5-6	6	5	70	47	101	107	Fast-on 187	0,86	20
CT 7-6	6	7	151	34	94	100	Fast-on 187	1,28	8
CT 12-6L	6	12	151	50	94	100	Fast-on 250	2,05	8
CT 12-6	6	12	151	50	94	100	Fast-on 187	2,05	8
CT 20-6	6	20	157	83	125	125	Fast-on 250	-	-
CT 0.8-12	12	0,8	96	25	62	62	konektor	0,34	20
CT 1.2-12	12	1,2	97	43	52	59	Fast-on 187	0,6	24
CT 2.0-12NP	12	2	150	20,5	89,5	89,5	Fast-on 187	0,74	20
CT 2.1-12	12	2,1	178	35	60	67	Fast-on 187	1	20
CT 2.3-12C	12	2,3	182	24	61,7	61,7	Fast-on 187	-	-
CT 2.6-12	12	2,6	70	48	104	104	Fast-on 187	-	-
CT 2.9-12	12	2,9	79	55	102	102	Fast-on 187	-	-
CT 3.4-12	12	3,4	134	67	60	67	Fast-on 187	1,4	10
CT 5-12	12	5	90	70	101	107	Fast-on 187	1,7	10
CT 5-12L	12	5	90	70	101	107	Fast-on 250	1,83	10
CT 6-12HR	12	6	151	50	98	102	Fast-on 187	-	-
CT 7-12	12	7	151	65	94	100	Fast-on 187	2,54	5
CT 7-12L	12	7	151	65	94	100	Fast-on 250	2,54	5
CT 7.5-12HR	12	7,5	151	65	94	100	Fast-on 250	2,6	5
CT 9-12L	12	9	151	65	94	100	Fast-on 250	2,66	5
CT 12-12	12	12	151	98	94	100	Fast-on 187	4,05	4
CT 12-12L	12	12	151	98	94	100	Fast-on 250	4,05	4
CT 14-12	12	14	151	98	94	100	Fast-on 250	4,3	4
CT 17-12	12	17	181	76	167	167	M5	6,06	2
CT 18-12HR	12	18	181	76	167	167	M5	6,06	2
CT 24-12	12	24	166	175	125	125	M5	8,2	1
CT 24-12s	12	24	166	125	175	182	M5	8,2	1
CT 33-12	12	33	194	130	166,5	166,5	M6	10,8	1
CT 38-12	12	38	197	165	170	170	M6	13,8	1
CT 55-12	12	55	228	137	210	214	M6	19	1
CT 65-12	12	65	350	166	174	174	M6	22,2	1
CT 65-12S	12	65	260	168	210	214	M6	22	1
CT 65-12HR	12	65	278	175	190	190	M6	22	1
CT 80-12	12	80	260	168	210	214	M6	25	1
CT 100-12	12	100	330	173	220	220	M6	34	1
CT 120-12	12	120	410	177	225	225	M6	37,6	1
CT 150-12	12	150	485	170	242	242	M8	-	1
CT 200-12	12	200	522	240	218	224	M8	65	1



FULGUR BATTMAN spol. s r.o.

www.fulgurbattman.cz

SVITAVSKÁ 39 · BRNO · 614 00 · TELEFON: +420 545 197 108 · FAX: +420 545 197 120 · EMAIL: info@fulgurbattman.cz

Bezúdržbové olověné akumulátory



CTL série

AGM
Předpokládaná životnost 10 let při teplotě 20°C



typ	napětí [V]	kapacita [Ah]	délka [mm]	šířka [mm]	výška [mm]	celková výška	připojení	váha [kg]	balení
CTL 7-12	12	7	151	65	94	100	Fast-on 250	2,5	5
CTL 12-12	12	12	151	98	94	100	Fast-on 250	4	4
CTL 18-12	12	18	181	76	167	167	M5	6,25	2
CTL 26-12	12	26	166	176	126	126	M5	9,2	1
CTL 28-12	12	28	166	125	175	175	M5	9,4	1
CTL 33-12	12	33	195	130	160	160	M6	10,9	1
CTL 44-12	12	44	197	165	170	170	M6	13,6	1
CTL 55-12	12	55	228	137	207	207	M6	17,5	1
CTL 70-12	12	70	350	167	179	179	M6	22,1	1
CTL 70-12s	12	70	259	168	208	208	M6	21,5	1
CTL 80-12	12	80	259	168	208	208	M6	23,7	1
CTL 100-12	12	100	305	168	208	208	M6	30	1
CTL 110-12	12	110	332	174	213	213	M6	32	1
CTL 120-12	12	120	408	176	227	227	M6	35	1
CTL 135-12	12	135	340	173	280	280	M6	39,6	1
CTL 150-12	12	150	482	170	242	242	M6	44,2	1
CTL 160-12	12	160	530	209	214	214	M8	-	1
CTL 200-12	12	200	520	240	220	220	M8	66	1
CTL 230-12	12	230	521	269	203	203	M8	-	1
CTL 110-6	6	110	193	168	205	205	M6	16	1
CTL 160-6	6	160	298	171	226	226	M6	26	1
CTL 200-6	6	200	318	170	225	225	M8	31	1

CTC série

Gelové, cyklické



typ	napětí [V]	kapacita [Ah]	délka [mm]	šířka [mm]	výška [mm]	celková výška	připojení	váha [kg]	balení
CTC 14-12	12	14	150	98	99	102	Fast-on 250	4	4
CTC 18-12	12	18	181	76	167	167	M5	6,2	2
CTC 26-12	12	26	165	175	125	125	M5	9,2	1
CTC 33-12	12	33	194	130	167	167	M6	10,4	1
CTC 44-12	12	44	196	164	170	170	M6	14	1
CTC 55-12	12	55	228	168	207	207	M6	17,5	1
CTC 65-12	12	65	278	175	190	190	M6	21,5	1
CTC 80-12	12	80	259	168	208	208	M6	23,3	1
CTC 100-12	12	100	305	168	208	208	M6	28,2	1
CTC 110-12	12	110	332	174	213	213	M6	32,2	1
CTC 135-12	12	135	340	173	280	280	M6	39,8	1
CTC 180-6	6	180	243	188	276	276	M8	32	1



FULGUR BATTMAN spol. s r.o.

www.fulgurbattman.cz

SVITAVSKÁ 39 · BRNO · 614 00 · TELEFON: +420 545 197 108 · FAX: +420 545 197 120 · EMAIL: info@fulgurbattman.cz

Bezúdržbové olověné akumulátory



CTV série

Gelové
Předpokládaná životnost 10 let při teplotě 20°C



typ	napětí [V]	kapacita [Ah]	délka [mm]	šířka [mm]	výška [mm]	celková výška	připojení	váha [kg]	balení
CTV 7-12	12	7	151	65	99	101	Fast-on 250	2,5	5
CTV 12-12	12	12	151	97	100	101	Fast-on 250	4	4
CTV 18-12	12	18	181	76	167	167	M5	5,9	2
CTV 26-12	12	26	166	176	126	126	M5	8,8	1
CTV 33-12	12	33	195	130	160	160	M6	10,9	1
CTV 44-12	12	44	197	165	170	170	M6	15	1
CTV 55-12	12	55	228	137	207	207	M6	17,5	1
CTV 70-12	12	70	350	167	179	179	M6	22,1	1
CTV 70-12s	12	70	259	168	208	208	M6	21,5	1
CTV 80-12	12	80	259	168	208	208	M6	23,3	1
CTV 100-12	12	100	305	168	208	208	M6	28,4	1
CTV 110-12	12	110	332	174	213	213	M6	32,2	1
CTV 120-12	12	120	408	176	227	227	M6	35,4	1
CTV 135-12	12	135	340	173	280	280	M6	39,8	1
CTV 150-12	12	150	482	170	242	242	M6	44,3	1
CTV 160-12	12	160	530	209	214	214	M8	-	1
CTV 200-12	12	200	520	240	220	220	M8	66	1
CTV 230-12	12	230	521	269	203	203	M8	-	1
CTV 110-6	6	110	193	168	205	205	M6	16	1
CTV 160-6	6	160	298	171	226	226	M6	26	1
CTV 200-6	6	200	318	170	225	225	M8	31	1

CTL, CTV (FT) série

Frontterminal



typ	napětí [V]	kapacita [Ah]	délka [mm]	šířka [mm]	výška [mm]	připojení	váha [kg]	balení
CTL 55-12FT	12	55	280	105	225	M6	-	1
CTL 80-12FT	12	80	560	113	181	M6	-	1
CTL 95-12FT	12	95	505	110	225	M6	-	1
CTL 100-12FT	12	100	395	110	285	M6	-	1
CTL 150-12FT	12	150	550	110	285	M6	-	1
CTL 180-12FT	12	180	530	125	320	M6	-	1
CTV 50-12FT	12	50	280	105	225	M6	-	1
CTV 70-12FT	12	70	560	113	181	M6	-	1
CTV 90-12FT	12	90	505	110	225	M6	-	1
CTV 100-12FT	12	100	395	110	285	M6	-	1
CTV 150-12FT	12	150	550	110	285	M6	-	1
CTV 170-12FT	12	170	530	125	320	M6	-	1



FULGUR BATTMAN spol. s r.o.

www.fulgurbattman.cz

SVITAVSKÁ 39 · BRNO · 614 00 · TELEFON: +420 545 197 108 · FAX: +420 545 197 120 · EMAIL: info@fulgurbattman.cz

typ	napětí [V]	kapacita [C100]	Wh/Z [100h]	délka [mm]	šířka [mm]	výška [mm]	připojení	váha [kg]	balení
CTS 9-12L	12	8,3	16,6	151	65	99	Fast-on 250	-	5
CTS11-12L	12	11	22	151	97	99	Fast-on 250	-	4
CTS 18-12	12	17,6	35	181	76	167	M5	-	2
CTS 28-12	12	28,1	56,2	166	176	125	M5	-	1
CTS 35-12	12	35	69,9	195	130	160	M6	-	1
CTS 44-12	12	43,9	87,6	197	165	170	M6	-	1
CTS 57-12	12	56,4	113	228	137	207	M6	-	1
CTS 69-12	12	68,6	137	350	167	179	M6	-	1
CTS 81-12	12	81	162	259	168	208	M6	-	1
CTS 98-12	12	97,9	195	305	168	208	M6	-	1
CTS 114-12	12	114	227	332	174	213	M6	-	1
CTS 124-12	12	124	247	408	176	227	M6	-	1
CTS 149-12	12	149	297	340	173	280	M6	-	1
CTS 154-12	12	154	308	482	170	242	M6	-	1
CTS 170-12	12	170	339	530	209	214	M8	-	1
CTS 206-12	12	206	411	520	240	220	M8	-	1
CTS 237-12	12	237	474	521	269	203	M8	-	1
CTS 191-6	6	191	382	260	180	250	M6	-	1
CTS 237-6	6	237	474	243	188	276	M8	-	1

Kde nás najdete:

