



## **ANSMANN APS 2250L**

Universal power supply 5 - 15 V DC to power many small electrical devices

## **Features**

- 5 15 V DC universal power supply to power many small electrical devices
- Regulated output voltage
- Short circuit proof
- World wide application possible due to wide range input (100-240V AC)
- Selectable output voltages by a rotary switch: 5V / 6V / 7,5V / 9V / 12V / 13,5V / 15V DC;
- Maximum output current: 2250mA bei 5-12V, 1800mA bei 13,5-15V;
- Maximum output power: 27 W



Voltage



Cable length



Charging current



Polarity inverter



Years Warranty\*

Powei



Adjustable Voltage





Article number: 1201-0025

**Product** APS 2250L, EU power plug with 2m cable, content: 7 changeable adapters with 1.8m cable

Customs tariff 85044082900

number:

Packing Unit:  $56 (600 \times 350 \times 270 \text{ mm})$ 



## **Specifications**

| Input voltage                  | 100 - 240V AC |         |        |
|--------------------------------|---------------|---------|--------|
| Max. output current            | 2,25 A        |         |        |
| suitable for                   | Universal     |         |        |
| Maximum power                  | 27 W          |         |        |
| Charging currents              | Voltage       | Current | Power  |
|                                | 5,0 V         | 2,25 A  | 11,3 W |
|                                | 6,0 V         | 2,25 A  | 13,5 W |
|                                | 7,5 V         | 2,25 A  | 16,9 W |
|                                | 9,0 V         | 2,25 A  | 20,3 W |
|                                | 12,0 V        | 2,25 A  | 27,0 W |
|                                | 13,5 V        | 1,8 A   | 24,3 W |
|                                | 15,0 V        | 1,8 A   | 27,0 W |
| Secondary plug set             | Yes           |         |        |
| Polarity socket                | Yes           |         |        |
| Stabilized                     | Yes           |         |        |
| Voltage range                  | 5 - 15 V DC   |         |        |
| Average operational efficiency | 80,0 %        |         |        |
| Efficiency at low load         | 77,8 %        |         |        |
| Power consumption at no load   | 0,050 W       |         |        |
| Color                          | black         |         |        |
| Packaging                      | cardboard box |         |        |
| Operating temperature          | 0 - 25 °C     |         |        |
| Storage temperature            | -25 - 70 °C   |         |        |