

9061 Max. 27 W

MULTIPLE OUTPUT POWER SUPPLIES

- Sikret mot polvending (inngang)
- Overspenningsbeskyttet (utgang)
- 6,3 mm flatstiftkontakter (inn- og utgang)
- Felles minus for inn- og utgang
- "E"-merket for kjøretøy direktivet (95/54/EC)
- Protected against reversed polarity (input)
- Protected against overvoltage (output)
- 6,3 mm push-on terminals (input and output)
- Common negative connection for input and output
- "E"-marked vehicle directive ref. (95/54/EC)



Tekniske data - 24/12 V versjon	Technical specifications - 24/12 V version	
Inngangsspenning:	<i>Input voltage:</i>	20-32 VDC
Utgangsspenning:	<i>Output voltage:</i>	13,5 VDC
Maks. utgangseffekt	<i>Max. output power</i>	
• Kontinuerlig:	• <i>Continuous:</i>	27 W
• Kortvarig:	• <i>Intermittent:</i>	40 W
Laststrøm	<i>Load current</i>	
• Kontinuerlig (-20°C - +25°C):	• <i>Continuous (-20°C - +25°C):</i>	2,0 A
• Kortvarig:	• <i>Intermittent:</i>	3,0 A
• Lineært avtagende til (ved +60°C):	• <i>Linearly derating to (at +60°C):</i>	1,0 A
Lastregulering (0-2,0 A last og 24 VDC inngangsspenning):	<i>Load regulation (0-2,0 A load and 24 VDC input voltage):</i>	< 5,0%
Linjeregulering (20-32 V inngangsspenning og 2 A last):	<i>Line regulation (20-32 V input voltage and 2 A load):</i>	< 5,0%
Tomgangsstrøm ca.:	<i>No load current approx.:</i>	8 mA
Temperaturområde:	<i>Temperature range:</i>	-20°C - +25°C
EMC standarder	<i>EMC standards</i>	
• Emisjon:	• <i>Emission:</i>	EN 61000-6-3,95/54/EC
• Immunitet:	• <i>Immunity:</i>	EN 61000-6-1,95/54/EC
Mål (LxBxH):	<i>Dimensions (LxWxH):</i>	80 x 105 x 46 mm
Vekt:	<i>Weight:</i>	250 g

Visse tekniske data kan variere for de forskjellige spenningsversjoner.
Some technical specifications may differ for other voltage versions.

Spenningsversjoner 9061 - Voltage versions 9061

Versjon Version	Inngang (VDC) Input (VDC)	Utgang (VDC) Output (VDC)	Maks. strøm (A) Max. current (A)	
			Kontinuerlig Continuous	Kortvarig Intermittent
12 / 5	8-16	5	1	1,4
12 / 6	10-16	6	3	4
12 / 7,5	10-16	7,5	3	4
12 / 9	10-16	9	3	4
24 / 6	20-32	6	1,5	3
24 / 7,5	20-32	7,5	1,6	3
24 / 9	20-32	9	1,7	3
24 / 12	20-32	13,5	2	3
24 / 12 (backup)	20-32	13,5 (14,5 backup)	2	3 (1 A backup)

23052006

www.mascot.no
sales@mascot.no
Phone:
Fax:

Main Office
PO Box 177
N-1601 FREDRIKSTAD
NORWAY
+47 69 36 43 00
+47 69 36 43 01

Mascot UK
Box 2090, Salisbury
Wiltshire SP2 2BH
UK
+44 1722 504 853
+44 845 299 1210

Mascot DE-AT-CH-BENELUX
Hirschbergstr. 28/7
D-74838 LIMBACH
GERMANY
+49 6287 95140
+49 6287 95141

Tettninger Str. 52
D-88239 WANGEN
GERMANY
+49 7528 95 16 77
+49 7528 95 16 78

Mascot France
38 rue Leo Lagrange
94270 Le Kremlin Bicêtre
FRANCE
+33 1 46 58 71 85
+33 1 46 58 71 85