

8860

Max. 75 W

DC/DC CONVERTERS - SWITCH MODE - WITH ELECTRICAL SEPARATION - UNREGULATED

- Sikret mot polvending og overspenning. 6,3 A sikring (inngang)
- Termisk sikret, kortslutningssikker og overspenningsbeskyttet ved ca. 16 V (utgang)
- 6,3 mm flatstiftkontakter (inngang og utgang)
- Spesielt beregnet for mobiltelefoner
- "E"-merket for kjøretøy direktivet (95/54/EC)
- Protected against reversed polarity and overvoltage. 6,3 A fuse (input)
- Thermal protection, short circuit proof and overvoltage protection at approx. 16 V (output)
- 6,3 mm push-on terminals (input and output)
- Specially designed for mobile telephones
- "E"-marked vehicle directive ref. (95/54/EC)



Tekniske data	Technical specifications	
Inngangsspenning:	Input voltage:	22-32 VDC
Utgangsspenning:	Output voltage:	13,3 VDC
Maks. utgangseffekt:	Max. output power:	75 W
Laststrøm:	Load current:	6,0 A
Lastregulering (0-6,0 A last og 24 VDC inngangsspenning):	Load regulation (0-6,0 A load and 24 VDC input voltage):	< 3,0%
Linjeregulering (22-32 V inngangsspenning og 6 A last):	Line regulation (22-32 V input voltage and 6 A load):	< 2,0%
Svitsjefrekvens ca.:	Switch frequency approx.:	30 kHz
Tomgangsstrøm ca.:	No load current approx.:	35 mA
Temperaturområde:	Temperature range:	-20°C - +40°C
Rippel (6 A last og 28 V inngangsspenning):	Ripple (6 A load and 28 V input voltage):	3 mV RMS
Virkningsgrad:	Efficiency:	80%
EMC standarder	EMC standards	
• Emisjon:	• Emission:	EN 61000-6-3,95/54/EC
• Immunitet:	• Immunity:	EN 61000-6-1,95/54/EC
Mål (LxBxH):	Dimensions (LxWxH):	96 x 115 x 38 mm
Vekt:	Weight:	400 g

23052006

www.mascot.no
sales@mascot.no

Phone:
Fax:

Main Office
PO Box 177
N-1601 FREDRIKSTAD
NORWAY
+47 69 36 43 00
+47 69 36 43 01

Mascot UK
Box 2090, Salisbury
Wiltshire SP2 2BH
UK
+44 1722 504 853
+44 845 299 1210

Mascot DE-AT-CH-BENELUX
Hirschbergstr. 28/7
D-74838 LIMBACH
GERMANY
+49 6287 95140
+49 6287 95141

Tettninger Str. 52
D-88239 WANGEN
GERMANY
+49 7528 95 16 77
+49 7528 95 16 78

Mascot France
38 rue Leo Lagrange
94270 Le Kremlin Bicêtre
FRANCE
+33 1 46 58 71 85
+33 1 46 58 71 85