


8613

Max. 4,8 W

AC/DC ADAPTERS - REGULATED

- Plugg-inn enhet
- Faste utgangsspenninger
- Termosikring i transformator og termisk beskyttelse i regulator
- Utskiftbare plugger
- Plug-in unit
- Fixed output voltages
- Thermal fuse in transformer and thermal protection in the regulator
- Exchangeable output plugs



Tekniske data	Technical specifications	
Inngangsspenning:	<i>Input voltage:</i>	230 VAC +6/-10%, 50/60Hz
Utgangsspenning:	<i>Output voltage:</i>	5-24 VDC
Maks. utgangseffekt:	<i>Max. output power:</i>	4,8 W
Rippel:	<i>Ripple:</i>	< 30 mV p-p
Isolasjonsklasse:	<i>Insulation class:</i>	II
Elektrisk sikkerhetsstandard:	<i>Electrical safety standard:</i>	EN 60065, EN 60950
EMC standarder	<i>EMC standards</i>	
• Emisjon:	• <i>Emission:</i>	EN 61000-6-3
• Immunitet:	• <i>Immunity:</i>	EN 61000-6-1
Utgangsterminaler	<i>Output terminals</i>	
• Sek. ledning med/uten plugg:	• <i>Cord with/without plug:</i>	Tilbehør / Accessories
Mål uten plugg (LxBxH):	<i>Dimensions without plug (LxWxH):</i>	95 x 51 x 57 mm
Vekt:	<i>Weight:</i>	420 g

Spenningsversjon (VDC) Voltage version (VDC)	Maks. last (mA) Max. load (mA)
5	700
6	600
7,5	600
9	500
12	400
15	340
18	280
24	210