

6820-8930

Max. 31 VA

AC/AC POWER SUPPLY LINEAR

- Faste utgangsspenninger
- Termosikring i transformator
- Nettledning
- Sekundærledning eller snappkontakt
- Kan leveres med festebrakett
- *Fixed output voltages*
- *Thermal fuse in transformer*
- *Mains cord*
- *Cord or snap terminals*
- *Mounting bracket available*



<u>Tekniske data</u>	<u>Technical specifications</u>		6820	8930
Inngangsspenning:	<i>Input voltage:</i>	VAC	230 VAC +6/-10%, 50/60Hz	
Maks. utgangseffekt:	<i>Output voltage:</i>	VA	25	31
Temperaturområde:	<i>Temperature range:</i>	C	-20 - +30	
Isolasjonsklasse:	<i>Insulation class:</i>		II	
Isolasjonsspenning:	<i>Insulation voltage:</i>	VAC	3000	3750
Elektrisk sikkerhetsstandard:	<i>Electrical safety standard:</i>		EN 60950	EN 60950
EMC standarder	<i>EMC standards</i>			EN 60742
• Emisjon:	• <i>Emission:</i>		EN 61000-6-3	
• Immunitet:	• <i>Immunity:</i>		EN 61000-6-1	
Mål:	<i>Dimensions:</i>	LxWxH mm	98x87x55	98x87x55
Vekt:	<i>Weight:</i>	g	920	950

Spenningsversjoner - Voltage versions

VDC	Maks. last / Max. load (A)	
	6820	8930
3	5,0	
4,5	5,0	
5	5,0	
6	4,1	5,0
7,5	3,3	4,1
9	2,7	3,4
12	2,0	2,5
15	1,6	2,0
18	1,4	1,7
21	1,2	1,4
24	1,0	1,2
36		0,86
42	0,6	0,73

Individuelle dataark er tilgjengelige på www.mascot.com
Individual data sheets are available at www.mascot.com

23052006

www.mascot.no
sales@mascot.no
Phone:
Fax:

Main Office
 PO Box 177
 N-1601 FREDRIKSTAD
 NORWAY
 +47 69 36 43 00
 +47 69 36 43 01

Mascot UK
 Box 2090, Salisbury
 Wiltshire SP2 2BH
 UK
 +44 1722 504 853
 +44 845 299 1210

Mascot DE-AT-CH-BENELUX
 Hirschbergstr. 28/7
 D-74838 LIMBACH
 GERMANY
 +49 6287 95140
 +49 6287 95141

Tettninger Str. 52
 D-88239 WANGEN
 GERMANY
 +49 7528 95 16 77
 +49 7528 95 16 78

Mascot France
 38 rue Leo Lagrange
 94270 Le Kremlin Bicêtre
 FRANCE
 +33 1 46 58 71 85
 +33 1 46 58 71 85